
STI MANUFACTURING, INC. STYLE 7RSpring LOADED

SHEATH TUBE TYPE RTD WITH FLEXIBLE INSULATED LEAD WIRE FOR MAXIMUM OPERATING TEMPERATURE OF 400 DEG. F. 22 ga. LEAD WIRE STANDARD, OTHER GAUGES AVAILABLE.



STI MANUFACTURING, INC. STYLE 7RS OPTIONS

INDUSTRIAL RTD HEADS





AVAILABLE **MATERIALS** CAST IRON **CAST ALUMINUM POLYPROPYLENE** *STAINLESS STEEL *SPECIAL ORDER


TERMINAL BLOCKS ARE CERAMIC PORCELAIN WITH BRASS TERMINALS

GROUND SCREWS ARE AVAILALBE-**SPECIFY UNDER ADDITIONL** REQUIREMENTS

EXPLOSION PROOF HEADS



EXPLOSION PROOF HEADS FMCSA CERTIFICATION NEMA 4 RATING





AVAILABLE MATERIALS CAST ALUMINUM *STAINLESS STEEL *EPOXY COATED

TERMINAL BLOCKS ARE BAKELITE

INDUSTRIAL RTD HEADS HINGED TYPE -WEATHER TIGHT SEAL **NEMA 4 RATING**

3/4" NPT CONDUIT 1/2" NPT INSTRUMENT




AVAILABLE MATERIALS CAST ALUMINUM POLYPROPYLENE

TERMINAL BLOCKS ARE CERAMIC PORCELAIN WITH BRASS TERMINALS

STANDARD 1/2" NPT SCH. 40 **GALVANIZED**




SPRING LOADING



STANDARD HEX NIPPLE



WELD PADS



TUBE TO PIPE FITTINGS STAINLESS STEEL STANDARD OTHER MATERIALS AVAILABLE

